



FIELDKING ROTARY TILLER (SINGLE SPEED)



BENEFITS :

- Suitable for use in dry as well as wet land cultivation.
- Suitable for light and medium soil conditions.
- Used for loosening and aerating soil up to a depth of 5-6 inches.
- Prepares seed beds quickly and economically.

FEATURES :

- Single speed gear box with 3 Point linkage, Compatible with 540 PTO RPM.
- Easy depth adjustment.
- Available in both gear driven and chain driven.
- Type of blade- L type.

SPECIFICATIONS

	FK 125	FK 150	FK 175	FK 200
TRACTOR POWER	40-45	45-50	50-55	55-65
OVERALL WIDTH	155 cm	180 cm	205 cm	230 cm
TILLAGE WIDTH	125 cm	150 cm	175 cm	200 cm
GEARBOX	SINGLE SPEED	SINGLE SPEED	SINGLE SPEED	SINGLE SPEED
P.T.O. SPEED (r.p.m.)	540	540	540	540
ROTOR SPEED	210	210	210	210
GEAR BOX OVERLOAD PROTECTION	SHEAR BOLT	SHEAR BOLT	SHEAR BOLT	SHEAR BOLT
MOUNTING HEIGHT	117 cm	117 cm	117 cm	117 cm
No. OF FLANGES	5	6	7	7
No. OF BLADES	30	36	42	48
TOTAL WT.	297 Kg. (Approx.)	337 Kg. (Approx.)	377 Kg. (Approx.)	417 Kg. (Approx.)

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Mfg. By:

BERI UDYOG PVT. LTD.

(AN ISO 9001-2000 COMPANY)

PLOT NO.100-101, SECTOR 3, HSIIDC, KARNAL (HARYANA) INDIA

PH: 00 91 184 2221571/72/73, FAX: 00 91 184 2221574

E-mail: info@fieldking.com, Homepage: www.fieldking.com