



FIELDKING ROTARY TILLER (MULTI SPEED GEAR DRIVE)







BENEFITS :

- * Fuel expenses saving can be to the tune of 18 to 39%.
- * It can immediately prepare the soil, the soil moisture of previous crop does not go waste.
- * Puddling in wet fields is done smoothly, quickly & efficiently.

FEATURES :

- * Long lasting blades made out of special quality wear resistant steel.
- * Sealed bearings prevent moisture/mud entry.
- * High Quality Drive Shaft
- * The well shaped adjustable rear trailing board.

SPECIFICATIONS

	FK 160	FK 180	FK 200			
TRACTOR POWER	35-45	40-50	45-60			
OVERALL WIDTH	170 cm	190 cm	210 cm			
TILLAGE WIDTH	160 cm	180 cm	200 cm			
GEARBOX	Multi (4 Speed)	Multi (4 Speed)	Multi (4 Speed)			
SIDE TRANSMISSION	Gear	Gear	Gear			
P.T.O. SPEED (r.p.m.)	540	540	540			
NO. OF BLADES	48	54	60			
GEAR BOX OVERLOAD PROTECTION	Shear Bolt	Shear Bolt	Shear Bolt			
				Gear	Size	Rotor (r.p.m.)
					16X20	170
					17x19	190
					19X17	238
					20X16	267

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Mfg. By:

BERI UDYOG PVT. LTD.

(AN ISO 9001-2000 COMPANY)

PLOT NO.100-101, SECTOR 3, HSIIDC, KARNAL (HARYANA) INDIA

PH: 00 91 184 2221571/72/73, FAX: 00 91 184 2221574

E-mail: info@fieldking.com, fieldking@gmail.com.

Homepage: www.fieldking.com