



## FIELDKING GROOMING MOWER



**FIELDKING Mowers** are Ideal for turf grass growers, golf courses, parks, and large recreational areas. FIELDKING mowers are available in widths of 4ft., 5 ft., 6 ft, and 7 ft.. These mowers are constructed of high quality components. FIELDKING Mowers can be operated at a high ground speed, and the units are very low maintenance making FIELDKING Mowers the right choice for cutting large parks.

### Features:-

- For tractors from 20 to 60 hp at 540 rpm
- Heavy duty transport frame
- Cutting Heights from 1 inches to 3 inches
- Pull type mower with high flotation transport tires
- Safety chain shield standard
- 5 mm reinforced mower decks
- 4 rubber bearing tires and Heavy duty, one piece, balanced steel pulleys
- High blade tip speed and precise blade overlap
- Two heavy duty reinforced belts, Single unit gearbox

### SPECIFICATION

	FK/GM/4F	FK/GM/5F	FK/GM/6F	FK/GM/7F
<b>Mowing width (in.)</b>	48	60	72	84
<b>Overall Width (in.)</b>	52	64	76	88
<b>Moving Height (in.)</b>	2"	2"	2"	2"
<b>Number of blades</b>	2	2	3	3
<b>Dock Material Thickness (mm)</b>	5	5	5	5
<b>Hitch</b>	Cat-I/II	Cat-I/II	Cat-I/II	Cat-I/II
<b>PTO Shaft Type</b>	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt
<b>PTO Power Required (HP)</b>	20-30	30-40	40-50	50-60
<b>Optimum PTO Speed (RPM)</b>	540	540	540	540
<b>Blade Speed (RPM)</b>	1034	1034	1034	1034
<b>Wheel Type</b>	Solid	Solid	Solid	Solid
<b>Approximate Weight with PTO (Kgs.) (Approx.)</b>	240	280	360	400

\*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Mfg. By:

**BERI UDYOG PVT. LTD.**

(AN ISO 9001-2000 COMPANY)

PLOT NO.100-101, SECTOR 3, HSIIDC, KARNAL (HARYANA) INDIA

PH: 00 91 184 2221571/72/73, FAX: 00 91 184 2221574

E-mail: [info@fieldking.com](mailto:info@fieldking.com), Homepage: [www.fieldking.com](http://www.fieldking.com)