



FIELDKING HEAVY DUTY SPRING LOADED TILLER



BENEFITS :

- Suitable for use in stone and root obstructed soil.
- It is designed for toughest operations.
- Used for loosening and aerating soil to a depth of nine inches.
- Prepares seed beds quickly and economically.

FEATURES :

- When one tyne strikes a hidden object, the others continue to work at the correct depth.
- Spring Loaded assemblies derive their strength from heavy-duty angles, which once fixed to the immensely strong main frame cannot move or strain out of position.

SPECIFICATIONS :

	9 TYNE	11 TYNE	13 TYNE	15 TYNE
FRAME	65X10 mm (Angle)	65X10 mm (Angle)	65X10 mm (Angle)	65X10 mm (Angle)
SPRING	9.5 mm WD, 50 mm OD 27 Coils	9.5 mm WD, 50 mm OD 27 Coils	9.5 mm WD, 50 mm OD 27 Coils	9.5 mm WD, 50 mm OD 27 Coils
TYNES	50 x 19 mm (Forged)	50 x 19 mm (Forged)	50 x 19 mm (Forged)	50 x 19 mm (Forged)
PAIRS	50X6 / 50X8 mm Flat	50X6 / 50X8 mm Flat	50X6 / 50X8 mm Flat	50X6 / 50X8 mm Flat
ANCHOR PIN	25 mm	25 mm	25 mm	25 mm
NUTS	Nylock	Nylock	Nylock	Nylock
FRAME BOLT	M 12 x 32 (High Tensile)	M 12 x 32 (High Tensile)	M 12 x 32 (High Tensile)	M 12 x 32 (High Tensile)
TYNE BOLT	M 16X90 mm (High Tensile)	M 16X90 mm (High Tensile)	M 16X90 mm (High Tensile)	M 16X90 mm (High Tensile)
LINKAGE 3 POINT	50 x 12 mm	50 x 12 mm	50 x 12 mm	50 x 12 mm
SHOVEL	8 mm EN-45	8 mm EN-45	8 mm EN-45	8 mm EN-45
LENGTH	2184 mm	2412 mm	2640 mm	2868 mm
WIDTH	900 mm	900 mm	900 mm	900 mm
HEIGHT	533 mm	533 mm	533 mm	533 mm
TILLER PIN	28 mm	28 mm	28 mm	28 mm
WEIGHT	235 Kg.	282 Kg.	330 Kg.	378 Kg.

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Mfg. By:

BERI UDYOG PVT. LTD.

(AN ISO 9001-2000 COMPANY)

PLOT NO.100-101, SECTOR 3, HSIIDC, KARNAL (HARYANA) INDIA

PH: 00 91 184 2221571/72/73, FAX: 00 91 184 2221574

E-mail: info@fieldking.com, Homepage: www.fieldking.com