



FIELDKING TIPPING TRAILER



SPECIFICATIONS:

Sr. No.	Description	5 Ton	9 Ton
1.	Outer Dimensions	10' x 6' x 1.75'	12' x 6' x 2.00'
2.	Main Chassis	150 X 75 mm M.S. Channel	200 X 75 mm M.S. Channel
3.	Second Chassis	100 X 50 mm M.S. Channel	125 X 65 mm M.S. Channel
4.	Support Channel	75 x 40 mm M.S. Channel	75 x 40 mm M.S. Channel
5.	Floor Platform	4 mm Thickness	4 mm Thickness
6.	Side Wall	2 mm Thickness Corrugated	2 mm Thickness Corrugated
7.	Front Door	Fixed by bolt and nuts and removable.	Fixed by bolt and nuts and removable.
8.	Side & Rear doors	Two side doors & one rear door. Both drop down and removable.	Two side doors & one rear door. Both drop down and removable.
9.	Wheel Rim	Heavy duty double plate	Heavy duty double plate
10.	Tyres	2 Nos. of 7.50 x 16 (9.00 x 16 optional)	2 Nos. of 9.00 x 16
11.	Painting	PU Paint	PU Paint
12.	Hydraulic Jack	10 Tons capacity heavy duty double stage tipping ram	15 Tons capacity heavy duty double stage tipping ram
13.	Hitch Beam	125 X 125 mm Tubular	125 X 125 mm Tubular
14.	Toe Eye	Forged steel hitch beam 50 mm dia.	Forged steel hitch beam 65 mm dia.
15.	Axle	75 mm Square	90 mm Square
16.	Axle Bearing (SKF)	32214 inner & 32213 outer	32216 inner & 32213 outer
17.	Hub	SGI Casting 500/7, CNC Machined	SGI Casting 500/7, CNC Machined

Mfg. By:

BERI UDYOG PVT. LTD.

(AN ISO 9001-2000 COMPANY)

PLOT NO.100-101, SECTOR 3, HSIIDC, KARNAL (HARYANA) INDIA

PH: 00 91 184 2221571/72/73, FAX: 00 91 184 2221574

E-mail: info@fieldking.com, Homepage: www.fieldking.com